



# Window Wall



Sleep Mode



Auto Restart



Auto Defrosting



Fresh Air



Anti-Cold Air Function



Timer



Independent Dehumidification

# Window Wall (R410A)

## Specifications: Window Wall (R410A)

Model		MWF1-09HMN1	MWF1-12HMN1	MWF-18HMN1	MWE-24HRN1
Power supply	Ph-V-Hz	1Ph,220-240V~ ,50Hz	1Ph,220-240V~ ,50Hz	1Ph,220-240V~ ,50Hz	1Ph,220-240V~ ,50Hz
Cooling performance					
Capacity	Btu/h	9000	12000	18000	24000
Input	W	1100	1450	1950	2330
Current	A	4.8	6.5	9	11
EER	W/W	2.4	2.4	2.4	2.8
Heating performance					
Capacity	Btu/h	9000	12000	18000	19000
Input	W	1000	1350	1800	2100
Current	A	4.4	5.8	8	10
COP	W/W	2.6	2.6	2.6	2.8
Unit Specifications					
Indoor air flow (Hi/Med/Lo)	m3/h	400/360/320	460/410/370	720/650/580	800/720/640
Noise level (Hi/Med/Lo)	dB(A)	55/52/50	52/49/47	54/52/50	60/57/55
Outdoor noise level (Hi/Med/Lo)	dB(A)	60/57/54	61/58/56	60/57/55	68/65/63
Dimension (WxDxH)	mm	450x535x346	600x560x380	660x680x428	660x780x428
Packing (WxDxH)	mm	495x580x435	685x620x430	746x815x515	770x915x510
Net/Gross weight	kg	28/30	36.3/39	53/57.5	62/66
Refrigerant type/quantity					
Refrigerant Type	Kg	R410A/0.65	R410A / 0.85	R410A / 1.1	R410A/1.4
Control type		Mechanical Control	Mechanical control	Mechanical control	Remote Control

### Remarks:

1. The above design and specifications are subject to change without prior notice for product improvement.
2. The sound levels in the table above reflect the levels as taken in an anechoic chamber.

### Dealer Details: